

## INERTIA EFFECT UNDER COUPLE STRESS FLUID IN LAMINAR FLOW CONDITION IN JOURNAL BEARING

SUGATO GHOSH<sup>1</sup> & ARTHUR MILLER<sup>2</sup>

<sup>1</sup>Calcutta Institute of Technology, Under West Bengal University of Technology, West Bengal, India

<sup>2</sup>International American University, Los Angeles, CA 90010 USA

### ABSTRACT

We derive the more fundamental equation where We focus on how to neglect inertia terms of the Navier Stokes equation, since this is well understood where the consideration of the additional viscous terms in the Navier Stokes equation is a topic of current research. We considered two examples for inertia term of Navier Stokes equation where We neglecting viscous term in driving the Reynolds equation for couple stress fluid which I can also proved to be important in some situation. First case any surface feature under couple stress fluid resulting in film geometry where  $\frac{\partial p}{\partial \theta} = 0(1)$  or  $\frac{\partial^2 p}{\partial \theta^2} = 0(1)$ . The singularity comes from the additive conjunction of blinding of additive moles at the curvature which is less serve than the one arising from the film gradient, but in both cases using the Reynolds equation will not allow a proper matching between the fluid regions. The second example implicated where the Reynolds equation will not describe what occur a solid particle is within the conjunction. The significant error is to be determining with inertia effect and without inertia effect between them in these research paper.

**KEYWORDS:** Order 1, Order  $\left(\frac{D}{L}\right)^2$ , Inertia Creation, Error Creation